

DC-60

For Earth, For Life
Kubota

Combine Harvester *For Rice*



COMPACT & EFFICIENT

OUTSTANDING FEATURES

- SUITABLE AND TESTED TO DRY AND WET PADDY HARVESTING
- COMBINES HARVESTING, THRESHING, CLEANING, AND BAGGING IN ONE OPERATION
- ALLOWS HARVESTING EVEN AT NIGHT
- LIGHTWEIGHT AND COMPACT
- EQUIPPED WITH HYDROSTATIC TRANSMISSION
- EASY TO OPERATE AND MANEUVER
- EASY TO MAINTAIN

Threshing Loss:
LESS THAN 3%

Maximized Productivity



SPECIFICATIONS

Dimensions	Length		mm	4800	
	Width		mm	2175	
	Height		mm	2800	
Weight			kg	2450	
Engine	Model			V2403DI-T	
	Type			Water Cooled, 4-Cycle, 4 Cylinder, Turbocharged Diesel Engine	
	Displacement		cc	2450	
	Output		hp/rpm	60/2700	
Fuel Tank	Capacity		L	60	
Track	Track Gauge		mm	1150	
	Crawler	Width x Length	mm	400 x 1545	
	Contact Pressure		kgf/cm ³	0.19	
	Minimum Ground Clearance		mm	255	
	Transmission			HST 2-Range (2F/2R)	
	Speed	Low (F/R)		m/s	0 - 1.30
		High (F/R)		m/s	0 - 1.80
	Turning System				Clutch and Break
Cutting	Gathering Width		mm	2000	
	Cutter Bar Width		mm	1905	
	Cutter Height Range		mm	19 - 800	
	Reel	Rotation Diameter x Width	mm	900 x 1828	
	Height Adjustment				Hydraulics
Threshing	Drum	System		Spiked Tooth Axial Flow	
		Diameter x Length	mm	620 x 1615	
		Revolutions	rpm	560	
	Concave Area		m ²	1.456	
	Cleaning				Oscillating, 3-Way Air Stream Cleaning System
Loss Ratio				Less than 3%	
Hopper	Capacity		kg	200	
	Outlet			2	
Electrical System				12 Volts Battery Starting, Lighting Equipment, and Alarms (Cooled Temperature, Battery Charge, Engine Oil, Hopper Full, & Tailings Clogging)	
Harvesting Capacity			ha/day	3 - 5	

KUBOTA Philippines, Inc.

Manila Head Office:

232 Quirino Highway, Baesa, Quezon City, Metro Manila
Tel. Nos.: (632) 4223500 to 03; Fax Nos.: (632) 4223504 to 61
E-mail: kpi_g.kpi@kubota.com

Davao Branch:

1 Yuta@Dabaw Bldg., Purok 38, Diversion Road, Ma-a, Davao City 8000
Tel. Nos.: (082) 2828160 to 61

Website: www.kubota.com.ph

Authorized Dealer: