

For Earth, For Life
Kubota

KUBOTA B2140S

DIESEL TRACTOR

with Rotary Tiller and Sugarcane Guard



**For Outstanding Performance
and Mobility in Sugarcane Plantations!**

SPECIFICATIONS

ENGINE

Model	D1005-E2-D3IT
Type	E-TVCS, Liquid-cooled, 3 cylinder diesel
No. of cylinder	3
Engine gross power	15.67 kW (21 Hp)
Fuel tank capacity	23 L

DIMENSIONS

Overall length (w/o 3P)	2390 mm	
Overall width	1000, 910 mm	
Overall height (w/ ROPS)	1940 mm	
Wheel base	1563 mm	
Minimum ground clearance	300 mm	
Tread	Front	700, 790 mm
	Rear	810, 900 mm
Weight	587 kg	

NOTE: All B-series tractors are equipped with safety emblems.

TRAVELING SYSTEM

Tire	Front	5-12
	Rear	8-18
Steering System	Recirculating ball type manual steering	
Transmission	Gear shift, 9 forward and 3 reverse	
Brake type	Wet disc type	
Min. turning radius (w/ brake)	2.1 m (6.9 feet)	
Clutch system	Dry single plate	

HYDRAULIC UNIT

Hydraulic control system	Position valve
3 point hitch	ISO Category 1N

PTO SYSTEM

Rear PTO	SAE 1-3/8, 6 splines
PTO/ Engine speed	540 (rpm) at 2504 (rpm), 980 (rpm) at 2510 (rpm)

WORKS PERFECTLY WITH THE FOLLOWING IMPLEMENT



ROTARY TILLER

Model	KRX71PH	
3-point link	CAT .1-3-point linkage	
Drive	Slide drive (Chain)	
Dimension	Total Length	950 mm
	Total Width	900 mm
	Total Height	928 mm
Weight (Including Universal Joint)	160 kg	
Width of Tilling	716 mm	

EASY ACCESS



OPERATION CONTROLS



OPERATOR'S SEAT



FULL HOOD OPENING



Kubota

kubota.com.ph





 Kubota Philippines



For details and inquiries:

Main Office: Kubota Philippines, Inc.
 232 Quirino Highway, Baesa, Quezon City, Metro Manila
 Tel. Nos.: (632) 8422-3500 to 03
 Fax Nos.: (632) 8422-3504 to 05
 Website: <https://kubota.com.ph>

Authorized Dealer: