

For Earth, For Life
Kubota

KUBOTA B2440S

DIESEL TRACTOR



Designed for Increased Mobility, Higher Torque, and Absolute
Fuel Efficiency Ideal for Sugarcane Farming

SPECIFICATIONS

ENGINE

Model	D1005-E4-D35T
Type	E-TVCS, Liquid-cooled, 3 cylinder diesel
No. of cylinder	3
Engine gross power	17.87 kW (23.96 Hp)
Fuel tank capacity	23 L

DIMENSIONS

Overall length (w/o 3P)	2410 mm	
Overall width	1015, 1105 mm	
Overall height (w/ ROPS)	1960 mm	
Wheel base	1563 mm	
Minimum ground clearance	325 mm	
Tread	Front	815 mm
	Rear	810, 900 mm
Weight	625 kg	

NOTE: All B-series tractors are equipped with safety emblems.

TRAVELING SYSTEM

Tire	Front	180/ 15D12
	Rear	8.3-20
Steering System	Integral type power steering	
Transmission	Gear shift, 9 forward and 3 reverse	
Brake Type	Wet disc type	
Min. turning radius (w/ brake)	2.1 m (6.9 feet)	
Clutch	Dry single plate	

HYDRAULIC UNIT

Hydraulic control system	Position valve
3 point hitch	ISO Category 1N

PTO SYSTEM

Rear PTO	SAE 1-3/8, 6 splines
PTO/ Engine speed	540 (rpm) at 2504 (rpm), 980 (rpm) at 2510 (rpm)

WORKS PERFECTLY WITH THE FOLLOWING IMPLEMENT



ROTARY TILLER

Model	FL1021C	
3-point link	CAT .1-3-point linkage	
Drive	Slide drive (Chain)	
Dimension	Total Length	950 mm
	Total Width	1190 mm
	Total Height	925 mm
Weight (Including Universal Joint)	195 kg	
Width of Tilling	1016 mm	
Number of Blades	8 each for right and left	

FULL HOOD OPENING



OPERATOR'S COCKPIT



OPERATION CONTROLS



Kubota

kubota.com.ph





 Kubota Philippines



For details and inquiries:

Main Office: Kubota Philippines, Inc.
 232 Quirino Highway, Baesa, Quezon City, Metro Manila
 Tel. Nos.: (632) 8422-3500 to 03
 Fax Nos.: (632) 8422-3504 to 05
 Website: <https://kubota.com.ph>

Authorized Dealer: