

For Earth, For Life
Kubota

KUBOTA M9540

DIESEL TRACTOR

NEW



KUBOTA INTELLIGENCE SOLUTION
YOUR NEWEST AGRIBUSINESS PARTNER



The all-power, turbocharged, fuel-efficient, workhorse designed,
to boost productivity and profit of any plantation!

SPECIFICATIONS

ENGINE

Model	V3800-DI-T
Type	Direct Injection, liquid cooled 4 cylinder
Number of cylinder	4
Net power	70.8 kW (95Hp)
Battery capacity	12 V
Fuel tank capacity	90L

DIMENSIONS

Overall length	3760 mm	
Overall width (Minimum tread)	2010 mm	
Overall height	2535 mm (Muffler)	
Wheel base	2250 mm	
Tread	Front	1660 mm
	Rear	1540 mm to 1940 mm
Minimum ground clearance	450 mm (Drawbar bracket)	
Weight	2710 kg	

NOTE: All M-series tractors are equipped with vertical muffler and safety emblem.

TRAVELING SYSTEM

Standard tire size	Front	12.4-24
	Rear	18.4-30
Clutch	Dry single plate	
Steering	Hydraulic Power Steering	
Braking System	Hydraulic Wet Discs	
Differential	Bevel gear with different lock (Rear)	

HYDRAULIC UNIT

Hydraulic control system	Position, draft (top link sensing) and mix control
Three point hitch	Category 2
Remote hydraulic control	One remote valve
Traction system	Swinging drawbar, adjustable in direction

PTO SYSTEM

Direction of turning	Clockwise, viewed from tractor rear
PTO engine speed	6 spline : 540/2202

WORKS PERFECTLY WITH THE FOLLOWING IMPLEMENT



Sugarcane Planter

Model	SP920
Implement Work	Planting Sugarcane Stem with Double Row
Stem Length	350 to 400 mm
Sugarcane Capacity	850 kg
Fertilizer Tank Capacity	50 kg
Dimension (WxLxH)	1874 x 2095 x 2245 (mm)
Body Weight	933 kg



Disc Plow

Model	DP264L
Disc Size	26 in. x 4 disc
Weight	590 kg
Average Plowing Depth	30 cm

OPERATION CONTROLS



ADJUSTABLE STEERING WHEEL



FULL HOOD OPENING



Kubota

kubota.com.ph

f i y t Kubota Philippines



For details and inquiries:

Main Office: Kubota Philippines, Inc.
232 Quirino Highway, Baesa, Quezon City, Metro Manila
Tel. Nos.: (632) 8422-3500 to 03
Fax Nos.: (632) 8422-3504 to 05
Website: <https://kubota.com.ph>

Authorized Dealer: