Kubota

NEW TRACTOR

45228



BOLDER LOOK. POWER IN EVERY TURN.

SPECIFICATIONS

		Model		L5228		
Drive System		modol	4WD			
PTO power*			kW (HP/PS)	31.7(42.6 / 43.1)		
	Maker		(***** =)	KUBOTA		
	Model			V2403-M-DI		
	Type			Direct injection, Vertical, Water-Cooled, 4-cycle diesel		
		r of cylinders		4		
	Bore and stroke mm			87 × 102.4		
Engine	Total di	splacement	L	2.434		
, and the second	Engine	gross power*	kW (HP/PS)	38.0(51.0 / 51.7)		
4	Engine	net power*	kW (HP/PS)	36.2(48.5 / 49.2)		
		revolution	rpm	2700		
	Maxim	um torque	N-m	164		
	Fuel			Diesel (Supports B7, B10 and B20 Diesel Fuel)		
	Fuel ta	nk	L	48		
	Engine	crankcase (with filter)	L	7.6		
Capacities	Engine	coolant	L	7		
	Transn	nission case	L	40		
	Overall length (without 3p)		mm	3200		
	Overall		mm	1495		
	Overall	height	mm	2049		
Dimensions	Wheel	base	mm	1925		
	Min. ground clearance		mm	400		
	Tread	Front	mm	1150		
	IIeau	Rear	mm	1155, 1225		
Weight			kg	1493		
	Tires Front			8-18		
		Rear		13.6 - 26		
Traveling	Clutch			Dry type single stage		
System	Steering			Hydrostatic power steering		
Oystein	Transmission			Gear shift, 8 forward and 8 reverse		
	Brake			Mechanical, Wet disk type		
	Min. turning radius (with brake) m			2.65		
	Max. lift force	Hydraulic control system		Position control		
		Pump capacity	L / min	30.5		
Hydraulic Unit		3-point hitch		Category 1		
		At lift points	kg	1300		
		24 in. (610 mm) behind lift points	kg	1053		
		System pressure MPa (kgf / cm		17.7(180)		
РТО	Rear PTO			SAE 1-3 /8, 6-splines		
	PTO / Engine speed rpm			540/2268, 750/2348		

INCREASED HORSEPOWER



LED LIGHTS



SYNCHROMESH MAIN GEAR



MORE DURABLE CHECK CHAIN





NEW BONNET DESIGN



AIR CLEANER ALERT NOTIFICATION



べっとって)
kubota.com.ph	

		kubota.com.				
_	_	_	_			

-	_	-				
O	ola	N K	ubota	a Ph	ilipp	ines

For details and inquiries:

Main Office: Kubota Philippines, Inc.

232 Quirino Highway, Baesa, Quezon City, Metro Manila (632) 8422-3500 to 03 (632) 8422-3504 to 05

Tel. Nos.: Website:

https://kubota.com.ph

Authorized Dealer:

Note: The company reserves the right to change the specifications without notice.